







-  Conventional marking technology
-  Scribe, stylus and dot-peening marking technology
-  Type-wheel marking technology
-  Laser-marking technology
-  Traceability
-  Special-purpose machines

312 Workshop unit

Technical data sheet

- Marking area size 65 x 51 mm (X/Y)
- Different marking processes: Scribe, stylus, dot-peening and Vibropeening
- DataMatrix coding (ECC200)
- Compact and solid workshop unit for flexible component marking
- Robust ballscrews and carriages with revolving ball guides in both axes
- Drive with powerful stepper motors









BMC controller (BORRIES marking-controller)

- Universal 2-/3-axis marking controller in compact housing
- With integrated full-graphic 10" touch display
- Dimensions: 355 x 225 x 236 mm
- Included in the scope of delivery



Area of application


The 312 workshop unit is ideal for a wide variety of applications in trade and industry, in which legible markings are required on materials such as steel and aluminium in the form of dot-peening, Data Matrix codings or simple scribing tasks. Thanks to its simple operation, the device is excellently suited for individual and standard markings, in quality assurance and in warehouse management. Despite its small dimensions, the 312 model offers a writing area of 65 x 51 mm. Single-line or multi-line marking is also possible in larger character heights. Quick-change, optional workpiece supports enable adaptation to almost all workpiece geometries. The compact BMC marking controller offers extensive possibilities for data input via PC, barcode scanner or PLC. It is also used for the simple creation and selection of marking jobs. The character heights and font width can be freely scaled.

-  Conventional marking technology
-  Scribe, stylus and dot-peening marking technology
-  Type-wheel marking technology
-  Laser-marking technology
-  Traceability
-  Special-purpose machines


Options

- Covering of the underside of the marker with a dirt cover
- Application-dependent positive stop

Positive stop for round components



Positive stop for flat components



Technical data

Properties	Dimensions, unit, explanation
Dimensions of built-in unit (W x D x H)	350 x 460 x 705 mm
Marking area size (X, Y)	65 x 51 mm
Weight of built-in unit (without controller)	Approx. 24 kg
Marking speed (depending on text size and form, marking process and motorisation)	Up to 6 characters/second
Character height	From 1 mm (in 0.1 mm steps)
Documentation	German, English or French Other languages optional
Marking tip penetration depth (depending on the material to be marked, marking head and process)	Approx. 0.01 – 0.5 mm (see marking head data sheet)
Font	DIN 1451, 7 x 5 dot-peening, scribe marking, stylus marking, Vibropeening, DataMatrix code, other fonts optional
Special characters, logos	Optional according to the template
Writing direction	Straight, angled or circular
Media supply	
Voltage supply via BMC supply unit with connection cable	Wide-range power supply integrated in the controller
Compressed air connection (supply pressure) with technically conditioned compressed air	Min. 5 bar (min. 75 psi) Dried, oil-free, filtered with 50 µm
Working pressure (marking pressure)	Min. 2 bar up to max. 4 bar (30 psi to max. 60 psi)

Subject to technical changes.

